



## Vormstukken met rubber type RDG

- Geperst verloopstuk in gegalvaniseerd staal met rubber
- Max. dia. 315 mm

### Bestelvoorbeeld

- **RDG , 250, 200**

Verklaring:

**RDG** = type van verloopstuk

**250** = grootste diameter van verloopstuk

**200** = kleinste diameter van verloopstuk

RDG	Afmetingen			
	Ø d1 [mm]	Ø d2 [mm]	lp d	[kg]
RDG 125/080	125	80	25	0.18
RDG 125/100	125	100	25	0.15
RDG 150/100	150	100	25	0.21
RDG 150/125	150	125	25	0.22
RDG 160/100	160	100	25	0.20
RDG 160/125	160	125	25	0.21
RDG 160/150	160	150	25	0.22
RDG 180/125	180	125	25	0.30
RDG 180/150	180	150	25	0.27
RDG 180/160	180	160	25	0.23
RDG 200/100	200	100	25	0.36
RDG 200/125	200	125	25	0.33
RDG 200/150	200	150	25	0.30
RDG 200/160	200	160	25	0.28
RDG 200/180	200	180	25	0.29
RDG 250/125	250	125	25	0.54
RDG 250/150	250	150	25	0.51
RDG 250/160	250	160	25	0.41
RDG 250/180	250	180	25	0.46
RDG 250/200	250	200	25	0.36
RDG 315/160	315	160	25	1.01
RDG 315/200	315	200	25	0.92
RDG 315/250	315	250	25	0.79
RDG 315/300	315	300	25	0.96